This blank page was inserted to preserve pagination.

Preliminary Report on The Larch Shared Language*

J. V. Guttag
MIT Laboratory for Computer Science
545 Technology Square
Cambridge, Massachusetts 02139

J. J. Horning
Xerox Corporation
3333 Coyote Hill Road
Palo Alto, California 94304

October 1983

ABSTRACT

Each member of the Larch family of formal specification languages has a component derived from a programming language and another component common to all programming languages. We call the former interface languages, and the latter the Larch Shared Language.

This report presents version 1.0 of the Larch Shared Language. It begins with a brief introduction to the Larch Project and the Larch family of languages. The next chapter presents most of the features of the Larch Shared Language and briefly discusses how we expect these features to be used. It should be read before reading either of the remaining two chapters, which are a self-contained reference manual and a set of examples.

Keywords: Algebraic specification, specification language

©J. V. Guttag and J. J. Horning
MIT

*This work was supported at Mit's Laboratory for Computer Science by DARPA under contract N00014-75-C-0661, and by the National Science Foundation under Grant MCS-811984 6, and at the Xerox Palo Alto Research Center by the Computer Science Laboratory.

Table of Contents

Context

The Larch Family of Languages

Status and Plans

An Introduction to the Larch Shared Language

Simple Algebraic Specifications

Getting Richer Theories

Combining Independent Traits

Combining Interacting Traits

Renaming and Exclusion

Assumptions

Consequences

IfThenElse and Equality

Some Further Examples

Larch Shared Language Reference Manual

Structure of Manual

Kernel Syntax

Simple Traits

Consequences and Exemptions

Constrains Clauses

Implicit Signatures and Partial OpForms

Mixfix Operators

Boolean Terms as Equations

External References

Modifications

Implicit Incorporation of Boolean, IfThenElse, and Equality

Semantic Checking

Reference Grammar for Larch Shared Language

Towards a Larch Shared Language Handbook

Preface

Conventions

Basic Properties of Single Operators, Including Binary Relations

Ordering Relations

Group Theory

Simple Numeric Types

Simple Data Structures

Container Properties

Container Classes

Generic Operators on Containers

Nonlinear Structures

Rings, Fields, and Numbers

Lattices

Enumerated Data Types

Display Traits

References

Context

The Larch Family of Languages

The Larch Project is developing tools and techniques intended to aid in the productive use of formal specifications of systems containing computer programs. Many of its premises and goals are discussed in [Guttag, Horning, and Wing 82].

We view a system as consisting of a state and mechanisms for changing and extracting information from that state. We choose to define the information contained in the state without reference to either how that information was created or how it will be used. Our specifications consist of two parts. In one, we specify the properties of values that may appear in system states, and in the second, the program modules that deal with those states.

A major component of the Larch Project is a family of specification languages. Each Larch language has a component particular to a specific programming language and another component common to all programming languages. We call the former *interface languages*, and the latter the *shared language*.

We use the interface languages to specify program modules. Specifications of the interface that one module presents to other modules often rely on notions specific to the programming language, e.g., its denotable values or its exception handling mechanisms. Each interface language deals with what can be observed about the behavior of programs written in a specific programming language. Its simplicity or complexity is a direct consequence of the simplicity or complexity of the observable state and state transformations of that programming language.

The shared language is algebraic. It is used to specify abstractions that are independent of both the program state and the programming language. The operators defined by an algebraic specification appear in specifications written in the interface languages, and in reasoning about such specifications, but they are not directly available to users of programs. The role of shared language specifications is similar to that of abstract models in some other styles of specification.

Some important aspects of the Larch family of specification languages are:

Composability of specifications. We emphasize the incremental construction of specifications from other specifications. The importance of such mechanisms is discussed in [Burstall and Goguen 77]. Larch has mechanisms for building upon and decomposing specifications as well as for combining specifications.

Emphasis on presentation. Reading specifications is an important activity. To assist in this process, we use composition mechanisms defined as operations on specifications, rather than on theories or models.

Interactive and integrated with tools. The Larch languages are designed for interactive use. They are intended to facilitate the interactive construction and incremental checking of specifications. The decision to rely heavily on support tools has influenced our language design in many ways.

Semantic checking. It is all too easy to write specifications with suprising implications. We would like many such specifications to be detectably ill-formed. Extensive checking while specifications are being constructed is an important aspect of our approach. Larch was designed to be used with a powerful theorem prover for semantic checking to supplement the syntactic checks commonly defined for specification languages. We have been influenced here by our experience with Affirm [Musser 80].

Programming language dependencies localized. We feel that it is important to incorporate many programming-language-dependent features into our specification languages, but to isolate this aspect of specifications as much as possible. This prompted us to design a single shared language that could be incorporated into different interface languages in a uniform way.

Shared language based on equations. The shared language has a simple semantic basis taken from algebra. Because of the emphasis on composability, checkability and interaction, however, it differs substantially from the "algebraic" specification languages we have used in the past.

Interface languages based on predicate calculus. Each interface language is based on assertions written in typed first-order predicate calculus with equality, and incorporates programming-language-specific features to deal with constructs such as side effects, exception handling, and iterators. Equality over terms is defined in the shared language; this provides the link between the two parts of a specification.

Status and Plans

We are still in the early phases of the Larch project. In addition to the work described in this report, interface languages for CLU and Mesa have been designed. [Wing 83] contains a detailed description of the semantics of the CLU interface language. The Mesa interface language has not been documented, but we have used it, in conjunction with the shared language, to specify the program level interface to the Cypress data base system. This is the largest specification we have attempted.

A primitive checker for the Shared Language has been implemented [Kownacki 83]. In addition to parsing specifications, this program checks various context sensitive constraints and provides mechanisms for "expanding" assumptions, importations, and inclusions. This checker is an interim tool. We designed our specification language in tandem with an editing and viewing tool. Many language design decisions were influenced by the presumption that specifications would be produced and read interactively using this tool. A first design is complete [Zachary 83], but implementation has yet to begin.

We are in the process of implementing term rewriting software [Forgaard 83], [Lescanne 83] that we hope will provide much of the theorem-proving capability needed for analyzing specifications. The definition of the Larch Shared Language calls for a number of checks for which there can be

no effective procedure. We have what we believe are useful procedures, based on sufficient or necessary (but not both) conditions, for some of these checks, e.g., consistency. We are working on procedures for the others, e.g., checking constrains clauses. This is a difficult task. Diagnostics present a particularly vexing problem: How should relatively complicated theorem-proving procedures report problems to users who are not familiar with either their internal structure or the theory underlying them?

It is always difficult to evaluate a language that has not been extensively used. The Larch Shared Language is especially hard to evaluate because it has been designed for use in an environment that we have not yet built. In addition to the specification of Cypress, we have written a number of small specifications. On the whole, we were pleased by the ease of constructing these specifications in Larch, and with the specifications themselves. While constructing them, we uncovered several errors by inspection; we are encouraged that most of these errors would have been detected automatically by the checks called for in the language definition. It will be some time, however, before we can draw any strong conclusions about the potential utility of Larch in software development.

An Introduction to the Larch Shared Language

1. Simple Algebraic Specifications

Most of the constructs in the Larch Shared Language are designed to assist in structuring specifications, for both reading and writing. The *trait* is our basic module of specification. Consider the following specification for tables that store values in indexed places:

TableSpec: **trait**

introduces
new: → Table
add: Table, Index, Val → Table
#∈#: Index, Table → Bool
eval: Table, Index → Val
isEmpty: Table → Bool
size: Table → Card

constrains new, add, ∈, eval, isEmpty, size **so that**
for all [*ind, ind1:* Index, *val:* Val, *t:* Table]
eval(add(*t*, *ind*, *val*) , *ind1*) = **if** *ind* = *ind1* **then** *val* **else** eval(*t*, *ind1*)
ind ∈ new = false
ind ∈ add(*t*, *ind1*, *val*) = (*ind* = *ind1*) | (*ind* ∈ *t*)
size(new) = 0
size(add(*t*, *ind*, *val*)) = **if** *ind* ∈ *t* **then** size(*t*) **else** size(*t*) + 1
isEmpty(*t*) = (size(*t*) = 0)

This example is similar to a conventional algebraic specification in the style of [Guttag and Horning 80] and [Musser 80]. The part of the specification following **introduces** declares a set of *operators* (function identifiers), each with its *signature* (the *sorts* of its domain and range). These signatures are used to sort-check *terms* (expressions) in much the same way as function calls are type-checked in programming languages. The remainder of the specification constrains the operators by writing equations that relate sort-correct terms containing them.

There are two things (aside from syntactic amenities) that distinguish this specification from a specification written in our earlier algebraic specification languages:

A name, TableSpec, is associated with the trait itself.

The axioms are preceded by a **constrains** list.

The name of a trait is logically unrelated to any of the names appearing within it. In particular, we do not use sort identifiers to name units of specification. A trait need not correspond to a single "abstract data type," and often does not.

The **constrains** list contains all of the operators that the immediately following axioms are intended to constrain. It is the responsibility of a specification checker to ensure that the specification conforms to this intent. The constrained operators will generally be a proper subset of the operators appearing in the axioms. In this example the **constrains** list informs us that the axioms are not to put any constraints on the properties of **if then else**, false, 0, 1, +, |, and =, despite their occurrence

in the axioms. The judicious use of **constrains** lists is an important step in modularizing specifications.

We associate a theory with every trait. A theory is a set of well-formed formulas (wff's) of typed first-order predicate calculus with equations as atomic formulas.

The theory, call it Th, associated with a trait written in the Larch Shared Language is defined by:

Axioms: Each equation, universally quantified by the variable declarations of the containing constrains clause, is in Th.

Inequation: ~(true = false) is in Th. All other inequations in Th are derivable from this one and the meaning of =.

First-order predicate calculus with equality: Th contains the axioms of conventional typed first-order predicate calculus with equality and is closed under its rules of inference.

The equations and inequations in Th are derivable from the presence of axioms in the trait—never from their absence. Th is deliberately small, because it is important to prove theorems before a specification is complete, and we wanted to limit the circumstances under which the addition of new operators and equations could invalidate previously proved theorems. Had we chosen to take the theory associated with either the initial or final interpretation of a set of equations (as in [ADJ 78] and [Wand 79]), this monotonicity property would have been lost.

2. Getting Richer Theories

While the relatively small theory described above is often a useful one to associate with a set of axioms, there are times when a larger theory is needed, e.g., when specifying an "abstract data type." **Generated by** and **partitioned by** give different ways of specifying larger theories.

Section 1 does not include an induction schema. This is an appropriate limitation when the set of generators for a sort is incomplete. Saying that sort S is **generated by** a set of operators, Ops, asserts that each term of sort S is equal to a term whose outermost operator is in Ops. One might, for example, say that the natural numbers are **generated by** 0 and successor and the integers **generated by** 0, successor, and predecessor. **Generated by** adds an inductive rule of inference.

This inductive rule and the clause Table **generated by** [new, add] can be used to derive theorems such as

$\forall t$: Table [(t = new) | ($\exists ind$: Index [$ind \in t$])],

that would otherwise not be in the theory.

Section 1 allows equations to be derived only by direct equational substitution, not by the absence of inequations. This is an appropriate limitation when the set of observers for a sort is incomplete. Saying that sort S is **partitioned by** a set of operators, Ops, asserts that if two terms of sort S are unequal, a difference can be observed using an operator in Ops. Therefore, they must be equal if they cannot be distinguished using any of the operators in Ops. This rule of inference adds new equations to the theory associated with a trait, thus reducing the number of equivalence classes in the equality relation.

This rule and the clause Table **partitioned by** [$\in$, eval] can be used to derive theorems such as

add(add(*t*, *ind*, *v*), *ind1*, *v*) = add(add(*t*, *ind1*, *v*), *ind*, *v*),

that would otherwise not be in the theory.

3. Combining Independent Traits

Our example contains a number of totally unconstrained operators, e.g., false and +. Such traits are not very useful. The most straightforward thing to do would be to augment the specification with additional clauses dealing with these operators. One way to do this is by trait *importation*. We might add to trait TableSpec:

imports Cardinal, Boolean

The theory associated with the importing trait is the theory associated with the union of all of the **introduces** and **constrains** clauses of the trait body and the imported traits.

Importation is used both to structure specifications to make them easier to read and to introduce extra checking. Operators appearing in imported traits may not be constrained in either the importing trait or any other imported trait. This guarantees that imported traits don't "interfere" with one another in unexpected ways. I.e., it guarantees that the theory associated with a trait is a *conservative extension* of each of the theories associated with its imported traits. (An extension, Th1, of a theory, Th2, is conservative if and only if every wff of the language of Th2 which is in Th1 is also in Th2.) Each imported trait can, therefore, be fully understood independently of the context into which it is imported.

As a syntactic amenity, trait Boolean is automatically imported into all other traits.

4. Combining Interacting Traits

While the modularity imposed by importation is often helpful, it can sometimes be too restrictive. It is often convenient to combine several traits dealing with different aspects of the same operator. This is common when specifying something that is not easily thought of as an abstract data type. Trait *inclusion* involves the same union of clauses as trait importation, but allows the included operators to be further constrained. Consider, for example:

Reflexive: **trait**
introduces #.rel#: T, T → Bool
constrains .rel **so that for all** [*t:* T]
t .rel *t* = true

Symmetric: **trait**
introduces #.rel#: T, T → Bool
constrains .rel **so that for all** [*t1, t2:* T]
t1 .rel *t2* = *t2* .rel *t1*

Transitive: **trait**
introduces #.rel#: T, T → Bool
constrains .rel **so that for all** [*t1, t2, t3:* T]
(((*t1* .rel *t2*) & (*t2* .rel *t3*)) ⇒ (*t1* .rel *t3*)) = true

Equivalence: **trait**
includes Reflexive, Symmetric, Transitive

Equivalence has the same associated theory as the less structured trait

Equivalence1: **trait**
introduces #.rel#: T, T → Bool
constrains .rel **so that for all** [*t1, t2, t3:* T]
t1 .rel *t1* = true
t1 .rel *t2* = *t2* .rel *t1*
(((*t1* .rel *t2*) & (*t2* .rel *t3*)) ⇒ (*t1* .rel *t3*)) = true

Any legal trait importation may be replaced by trait inclusion without either making the trait illegal or changing the associated theory. It does involve the sacrifice of the checking that ensures that the imported traits may be understood independently of the context in which they are used. We use importation when we can incorporate a theory unchanged, inclusion when we cannot.

5. Renaming and Exclusion

The specification of Equivalence in the previous section relied heavily on the coincidental use of the operator .rel and the sort identifier T in three separate traits. In the absence of such happy coincidences, renaming can force names to coincide, keep them from coinciding, or simply replace them with more suitable names.

The phrase

Tr **with** [x **for** y]

stands for the trait Tr with every occurrence of y (which must be either a sort or operator identifier) replaced by x. Notice that if y is a sort identifier this renaming may change the signatures associated with some operators.

Occasionally we wish to eliminate an operator altogether. The phrase

Tr **without** [op]

stands for the trait Tr without the declaration of op and without each axiom, **generated by**, and **partitioned by** in which op appears. We use **without** to remove an operator either so that we can later add another operator with the same name and signature but different properties or merely because it is superfluous and we want to spare readers the bother of looking at it.

If TableSpec contains the **generated by** and **partitioned by** of section 2, the specification

ArraySpec: trait
imports IntegerSpec
includes TableSpec **without** [size]
with [defined **for** #∈#, assign **for** add, read **for** eval,
Array **for** Table, Integer **for** Index]

stands for

ArraySpec: **trait**
imports IntegerSpec
introduces
new: → Array
assign: Array, Integer, Val → Array
defined: Integer, Array → Bool
read: Array, Integer → Val
isEmpty: Array → Bool
constrains new, assign, defined, read, isEmpty **so that**
Array **generated by** [new, assign]
Array **partitioned by** [defined, read]
for all [*ind, ind1:* Integer, *val:* Val, *t:* Array]
read(assign(*t, ind, val*), *ind1*) =
if *ind* = *ind1* **then** *val* **else** read(*t, ind1*)
defined(*ind*, new) = false
defined(*ind1*, assign(*t, ind, val*)) = ((*ind* = *ind1*) | defined(*ind1, t*))

Notice that in this specification isEmpty is totally unconstrained. In section 7 we discuss a checking mechanism that would call the lack of constraints on isEmpty to the specifier's attention. This would, presumably, provoke him either to add the axioms

isEmpty(new) = true
isEmpty(assign(*t, ind, val*)) = false

to his specification, or to add isEmpty to the **without** clause.

The use of **without** rather than some sort of hiding mechanism (as in [Burstall and Goguen 81]) may thus involve some extra work for the specifier. In return for this work, users of the specification are spared having to deal with the "hidden" operators, e.g., in proofs that use the specification. This

is consistent with our belief that specifiers should be encouraged to do things that will make life easier for users of their specifications.

The definition of **without** should make it clear that we are indeed operating on the text of traits (presentations) rather than on their associated theories. Consider adding these isEmpty axioms to TableSpec to form another trait, TableSpec1. TableSpec and TableSpec1 have the same associated theories, but

TableSpec **without** size

and

TableSpec1 **without** size

have rather different associated theories—in the latter, isEmpty is fully defined.

A final point raised by the examples of this section is the importance of distinguishing between the history of a specification (how it was constructed) and the structure presented to a reader. A reader familiar with TableSpec might prefer to read the first version of ArraySpec; others might find it distracting to have to understand the more general structure before understanding ArraySpec.

6. Assumptions

We often construct fairly general specifications that we anticipate will later be specialized in a variety of ways. Consider, for example,

```
MultiSetSpec: trait
    introduces
        {}: → MultiSet
        insert: MultiSet, Elem → MultiSet
        delete: MultiSet, Elem → MultiSet
        #∈#: MultiSet, Elem → Bool
    constrains {}, insert, delete, ∈ so that
        MultiSet generated by [ {}, insert ]
        MultiSet partitioned by [ delete, ∈ ]
        for all [ m: MultiSet, e, e1: Elem ]
            e ∈ {} = false
            e ∈ insert(m, e1) = (e = e1) | (e ∈ m)
            delete({}, e) = {}
            delete(insert(m, e), e1) =
                if e = e1 then m else insert(delete(m, e1), e)
```

We might specialize this to IntMultiSet by renaming Elem to Integer and including it in a trait in which operators dealing with Integer are specified, e.g.,

```
IntMultiSet: trait
    imports IntegerSpec
    includes MultiSetSpec with [ Integer for Elem ]
```

The interactions between MultiSetSpec and IntegerSpec are very limited. Nothing in MultiSetSpec places any constraints on the meaning of the operators that occur in IntegerSpec, e.g., 0, +, and <. Consider, however, extending MultiSetSpec to MultiSetSpec1 by adding an operator rangeCount,

MultiSetSpec1: **trait**
imports MultiSetSpec, Cardinal
introduces
rangeCount: MultiSet, Elem, Elem → Integer
#<#: Elem, Elem → Bool
constrains rangeCount **so that for all** [*e1, e2, e3:* Elem, *m:* MultiSet]
rangeCount({}, *e1*, *e2*) = 0
rangeCount(insert(*m*, *e3*), *e1*, *e2*) =
rangeCount(*m*, *e1*, *e2*) + (**if** (*e1* < *e3*) & (*e3* < *e2*) **then** 1 **else** 0)

MultiSetSpec1 places no constraints on the < operator. Suppose, however, that this is not what we intend. We might have definite ideas about the properties that < must have in any specialization, e.g., that it should define a total ordering. We could specify such a restriction by adding to MultiSetSpec1 the assumption (Ordered is defined in the Handbook section, on page 36):

assumes Ordered **with** [Elem **for** T]

In constructing the theory associated with MultiSetSpec1, the assumption would be treated as if Ordered **with** [Elem **for** T] had been included. This could be used to derive various properties of MultiSetSpec1, e.g., that rangeCount is monotonic in its last argument.

Whenever the augmented MultiSetSpec1 is imported or included in another trait, however, the assumption will have to be be discharged. In

IntMultiSet1: **trait**
includes MultiSetSpec1 **with** [Integer **for** Elem]
imports IntegerSpec

this would amount to showing that the (renamed) theory associated with Ordered is a subset of the theory associated with IntegerSpec. Often, the assumptions of a trait are used to discharge the assumptions of traits it **imports** or **includes**.

7. Consequences

We have now looked at those parts of the Larch Shared Language that determine the theory associated with a valid trait. That subset of the language contains some checkable redundancy; e.g., assumptions are checked when a trait is included or imported, and **constrains** lists are checked against the axioms associated with them. We now turn to a part of the language whose only purpose is to introduce checkable redundancy, in the form of assertions about the theory associated with a trait.

There are two kinds of consequence assertions:

That the theory associated with a trait contains another theory.

That the theory associated with a trait "adequately" defines a set of operators in terms of

other operators.

The first kind of assertion is made using **implies**. Consider, for example, adding to the augmented MultiSetSpec1,

implies for all [*m:* MultiSet, *e1*, *e2*, *e3:* Elem]

($e2 < e3$) ⇒ (rangeCount(*m*, *e1*, *e2*) ≤ rangeCount(*m*, *e1*, *e3*))

Implies can be used to indicate intended consequences of a specification, both for checking and to increase the reader's insight. The theory to be implied can be specified using the full power of the language, e.g., by using **generated by** and **partitioned by**, or by referring to traits defined elsewhere.

The second kind of assertion is made using **converts** [Ops]. This asserts that each term is provably equal to a term that does not contain operators in Ops. (We do not require this for terms containing variables of sorts appearing in **generated by** clauses.) Converts is used to say that the specification adequately defines a collection of operators.

A common problem with axiomatic systems is deciding whether there are "enough" axioms. **Converts** provides a way of making a checkable statement about the adequacy of a set of axioms. Consider, for example, adding to TableSpec:

converts [isEmpty].

This says that each term containing isEmpty, such as isEmpty(new) or isEmpty(add(new), *ind*, *val*)), is equal to another term that does not contain isEmpty.

Now consider adding to TableSpec the stronger assertion:

converts [isEmpty, eval].

Terms containing subterms of the form eval(new, *ind*) are not convertible to terms that do not contain eval, so an error message of the form

eval(new, *ind*) not convertible

would be generated. This would present a problem if we did not wish to add an axiom to resolve this incompleteness. We therefore provide a mechanism to allow specifiers to indicate that the unconvertibility of certain terms is acceptable. If TableSpec were modifed to include

exempts for all [*ind:* Index] eval(new, *ind*)

the checking associated with the **converts** would now require that the theory associated with TableSpec must contain either

an equation, t = t1, where t1 has no occurrences of isEmpty or eval, or

an equation t' = t1, where t' is a subterm of t, and t1 is an instantiation of eval(new, *ind*).

This checking ensures that each term containing operators in the **converts** list is either defined by the axioms (in terms of operators not in the list) or explicitly exempted. One use of **converts** is to allow the specification checker to notice unintended effects of **without**. As suggested in section 6, the failure of ArraySpec to fulfill the **converts** inherited from TableSpec would trigger error messages of the form:

isEmpty(new) not convertible

isEmpty(assign(*t*, *ind*, *val*)) not convertible.

8. IfThenElse and Equality

In our examples we made use of some apparently unconstrained operators: **if then else** and =, with a variety of signatures. In fact, the appearance of these operators leads to the implicit incorporation of the traits IfThenElse and Equality.

Whenever a term of the form **if** b **then** t1 **else** t2 occurs in a trait we replace the mixfix symbol **if then else** by the prefix symbol ifThenElse. If t1 and t2 are of the same sort, T1, we also import the trait IfThenElse **with** [T1 **for** T] into the enclosing trait.

Whenever a term of the form t1 = t2 occurs in a trait, if t1 and t2 are of the same sort, T1, we append the trait Equality **with** [T1 **for** T] to the consequences of the enclosing trait.

Specifications of these traits are:

```
IfThenElse: trait
        introduces ifThenElse: Bool, T, T → T
        constrains ifThenElse so that for all [ t1, t2: T ]
                ifThenElse(true, t1, t2) = t1
                ifThenElse(false, t1, t2) = t2
        implies converts [ ifThenElse ]
Equality: trait
        includes Equivalence with [ = for .rel ]
        constrains = so that T partitioned by [ = ].
```

9. Some Further Examples

The following series of examples is adapted from the Handbook chapter. We include them here to illustrate some ways in which the facilities introduced above can be used. In reading these specifications, keep in mind that they are not themselves ends, but rather means to write interface specifications.

Our first example is an abstraction of those data structures that "contain" elements, e.g., Set, Bag, Queue, Stack. We have found it useful both as a starting point for specifications of various kinds of containers, and as an assumption for generic operations. The crucial part of the trait is the **generated by**. It indicates that any term of sort C is equal to some term in which new and insert are the only operators with range C—even if this trait is included in one that introduces additional operators that return values of sort C. This means that any theorems proved by induction over new and insert will remain valid.

```
Container: trait                                % C's contain E's
        introduces
                new: → C
                insert: C, E → C
        constrains C so that C generated by [ new, insert ]
```

The next example incorporates Container as an assumption. Notice that it constrains new and insert as well as the operator it introduces, isEmpty. The **converts** indicates that this trait contains

enough axioms to adequately specify isEmpty. Because of the **generated by**, this can be proved by induction over terms of sort C, using new as the basis and insert(*c*, *e*) in the induction step.

IsEmpty: **trait**
assumes Container
introduces isEmpty: C → Bool
constrains isEmpty, new, insert **so that for all** [*c*: C, *e*: E]
isEmpty(new) = true
isEmpty(insert(*c*, *e*)) = false
implies converts [isEmpty]

The next two examples assume Container. The **exempts** indicate that should these traits be included into a trait that claims the convertibility of next or rest, that trait needn't convert the terms next(new) or rest(new).

Next: **trait**
assumes Container
introduces next: C → E
constrains next, insert **so that for all** [*e*: E]
next(insert(new, *e*)) = *e*
exempts next(new)

Rest: **trait**
assumes Container
introduces rest: C → C
constrains rest, insert **so that for all** [*e*: E]
rest(insert(new, *e*)) = new
exempts rest(new)

The next example specifies properties common to various data structures such as stacks, queues, priority queues, sequences, and vectors. It augments Container by combining it with IsEmpty, Next, and Rest. The **partitioned by** indicates that next, rest, and isEmpty are sufficient to define equality over terms of sort C. Since we have little information about next and rest, the **partitioned by** does not yet add much to the associated theory.

Enumerable: **trait**
imports IsEmpty, Next, Rest
includes Container
constrains C **so that** C **partitioned by** [next, rest, isEmpty]

The next example specializes Enumerable by further constraining next, rest, and insert. Sufficient axioms are given to convert next and rest. The axioms that convert isEmpty are inherited from the trait Enumerable, which inherited them from the trait IsEmpty.

```
PriorityQueue: trait
    assumes TotalOrder with [ E for T ]
    includes Enumerable
    constrains next, rest, insert so that for all [ q: C, e: E ]
        next(insert(q, e)) =
            if isEmpty(q) then e
            else if next(q) ≤ e then next(q) else e
        rest(insert(q, e)) =
            if isEmpty(q) then new
            else if next(q) ≤ e then insert(rest(q), e) else q
    implies converts [ next, rest, isEmpty ]
```

In a trait, such as PriorityQueue, that defines an "abstract data type" there will generally be a distinguished sort (C in this case) corresponding to the "type of interest" of [Guttag 75] or "data sort" of [Burstall and Goguen 81]. In such traits, it is usually possible to partition the operators whose range is the distinguished sort into "generators," those operators which the sort is **generated by**, and "extensions," which can be converted into generators. Operators whose domain includes the distinguished sort and whose range is some other sort are called "observers." Observers are usually convertible, and the sort is usually **partitioned by** one or more subsets of the observers and extensions.

The next example illustrates a specialization of Container that does not satisfy Enumerable. It augments Container by combining it with IsEmpty and Cardinal, and introducing two new operators. Notice that we **include** Container, because we intend to constrain operators inherited from it, but **import** IsEmpty and Cardinal, because we do not intend to constrain any operator inherited from them. **Constrains** C is a shorthand for a **constrains** clause listing all the operators whose signature includes C. The **partitioned by** indicates that count alone is sufficient to distinguish unequal terms of sort C. **Converts** [isEmpty, count, delete] is a stronger assertion than the combination of an explicit **converts** [count, delete] with the inherited **converts** [isEmpty].

```
MultiSet: trait
    assumes Equality with [ Elem for T ]
    imports IsEmpty, Cardinal
    includes Container with [ empty for new ]
    introduces count: Elem, C → Bool
        delete: Elem, C → C
    constrains C so that
        C partitioned by [ count ]
        for all [ c: C, e1, e2: E ]
            count(empty, e1) = 0
            count(insert(c, e1), e2) = count(c, e2) + (if e1 = e2 then 1 else 0)
            delete(empty, e1) = empty
            delete(insert(c, e1), e2) =
                if e1 = e2 then c else insert(delete(c, e2), e1)
    implies converts [ isEmpty, count, delete ]
```

The next example specifies a generic operator. It uses Enumerable as an assumption to delimit the applicability of this operator to containers for which it is possible to enumerate the contained elements. (To understand why we assume Enumerable rather than Container, imagine defining extOp for a MultiSet.) The **exempts** indictates that we do not intend to fully define the meaning of applying extOp to containers of unequal size. Notice that elemOp is totally unconstrained in this trait. This prevents us from having many interesting implications to state at this stage.

PairwiseExtension: **trait**

assumes Enumerable
introduces
elemOp: E, E → E
extOp: C, C → C
constrains extOp **so that for all** [*c1*, *c2:* C, *e1*, *e2:* E]
extOp(new, new) = new
extOp(insert(*c1*, *e1*), insert(*c2*, *e2*)) = insert(extOp(*c1*, *c2*), elemOp(*e1*, *e2*))
implies converts [extOp]
exempts for all [*c:* C, *e:* E]
extOp(new, insert(*c*, *e*)),
extOp(insert(*c*, *e*), new)

Now we specialize PairwiseExtension by binding elemOp to + over Cardinals:

PairwisePlus: **trait**

assumes Enumerable
imports Cardinal
includes PairwiseExtension **with** [*#* + *#* **for** elemOp, *#* + *#* **for** extOp, Card **for** E]
implies Commutative **with** [*#* + *#* **for** O, C **for** T]

The validity of the implication that + for sort C is commutative stems from the replacement of elemOp by + for sort Card, whose constraints (in trait Cardinal) imply its commutativity.

Larch Shared Language Reference Manual

0. Structure of Manual

In section 1 we present a grammar for the kernel subset of the Larch Shared Language.

In section 2 we define the context sensitive checking and the theory associated with each specification written in the kernel subset.

In section 3 we extend the kernel subset by introducing mechanisms for specifying intended consequences of a specification written in the kernel subset.

In sections 4-10 we define successive extensions of the language. We modify the grammar to introduce additional aspects of the language and describe any additional context sensitive checking required. We also provide a translation from the newly extended language to the previously defined subset. The result of this translation is subjected to all the applicable checking. The theory associated with any specification written in the full language is the same as the theory associated with its translation.

Section 11 describes additional checks, defined in terms of the theories associated with traits, that are associated with various language features. To be legal, a specification and each of the parts from which it is built must satisfy these checks as well as the context sensitive checks described earlier.

Finally, section 12 collects the reference grammar for the entire language.

1. Kernel Syntax

1.1. Syntactic conventions

|	alternative separator
{e}	e is optional
e*	zero or more e's
e*,	zero or more e's, separated by commas
e+	one or more e's
alpha	alpha is a nonterminal symbol
alpha	alpha is a terminal symbol
'(')	parentheses as terminal symbols
(e)	parentheses for grouping syntactic expressions

1.2. Grammar

trait ::= *traitId* : **trait** *traitBody*
traitBody ::= *simpleTrait*
simpleTrait ::= {*opPart*} *propPart**
opPart ::= **introduces** *opDcl**
opDcl ::= *opId* : *signature*
signature ::= *domain* → *range*
domain ::= *sortId**,
range ::= *sortId*
propPart ::= **asserts** *props*
props ::=*generators** *partitions** *axioms**
generators ::= *sortId* **generated** *bylist**,
partitions ::= *sortId* **partitioned** *bylist**,
bylist ::= **by** [*sortedOp**,]
sortedOp ::= *opDcl*
axioms ::= **for all** [*varDcl**,] *equation**
varDcl ::= *varId**, : *sortId*
equation ::= *term* = *term*
term ::= *sortedOp* { '(*term**, ') } | *varId*
opId ::= *alphaNumeric* + | *opForm*
opForm ::= { # } *opSym* (# *opSym*)* { # }
opSym ::= *specialChar* + | . *alphaNumeric* +
traitId ::= *alphaNumeric* +
sortId ::= *alphaNumeric* +
varId ::= *alphaNumeric* +

Comments start with % and terminate with end of line. They may appear after any token.

2. Simple Traits

2.1. Context sensitive checking

simpleTrait:

The sets of *varId*'s, *sortId*'s and *opId*'s appearing in a *trait* must be disjoint.

Every *sortId* appearing anywhere in a *simpleTrait* must appear in its *opPart*.

Every *sortedOp* appearing anywhere in a *simpleTrait* must appear in its *opPart*.

opDcl:

Each *opForm* must have the same number of #'s as the number of occurrences of *sortId's* in the *domain*.

generators:

The *range* of each *sortedOp* must be the *sortId* of the *generators*.

At least one *sortedOp* in each *bylist* must have a *domain* in which the *sortId* of the *generators* does not occur.

partitions:

The *domain* of each *sortedOp* must include the *sortId* of the *partitions*.

The *range* of at least one *sortedOp* in each *bylist* must be different from the *sortId* of the *partitions*.

axioms:

Each *varId* used in a *term* must appear in exactly one *varDcl*.

No *varId* may occur more than once in [*varDcl**,].

equation:

The sorts of both *term*'s must be the same, where

The sort of a *term* of the form *sortedOp* { '(*term**, ') } is the *range* of the *sortedOp*.

The sort of a *term* of the form *varId* is the *sortId* of the *varDcl* in which the *varId* is declared.

term:

In *sortedOp* { '(*term**, ') } the *domain* of the *sortedOp* must be the sequence of the sorts of the *terms* in *term**, .

2.2. Associated theory

We associate a theory with each *trait*. This section defines the theory associated with a *simpleTrait*.

A theory is a subset of the language:

wff ::= *term* = *term*
| "propositional formula"
| "first order quantified (with sorts) formula"

We adopt the conventional meanings of the equality symbol (=), the propositional connectives (&, |, ~, ⇒, ...), and the quantifiers (∀ and ∃).

The subset of *wff* that is the theory, call it Th, associated with a *simpleTrait* is defined by:

Axioms: Each *equation*, universally quantified by the *varDcl*'s of its containing *axioms*, is in Th.

Inequation: ~(true:→Bool = false:→Bool) is in Th.

First order predicate calculus with equality: Th contains the axioms of conventional typed first-order predicate calculus with equality and is closed under its rules of inference.

Induction: If the *trait* has a *generators* with *sortId* S and a *bylist* by $[op_1, ..., op_n]$, and P(s) is a wff with a free variable, s, of sort S, Th contains the wff

∀[s: S] P(s)

if for each op_i in $[op_1, \ldots, op_n]$

$Q_i \Rightarrow P(op_i(x_1, ..., x_k))$ is in Th, where

k is the arity of op_i,

the x_j's are variables that do not appear free in P, and

Q_i is the conjunction of $P(x_j)$, for each j such that the j^{th} argument of op_i is of sort S.

Reduction: If the *trait* has a *partitions* with *sortId* S and a *bylist* by $[op_1, ..., op_n]$, Th contains the wff

$\forall[s_1, s_2: S]\ (Q \Rightarrow s_1 = s_2)$

where Q is the conjunction, for each op_i in $[op_1, \ldots, op_n]$ and each j such that the j^{th} argument of op_i is of sort S, of

$\forall[x_1: S_1, \ldots, x_k: S_k]$ (Subst(op_i, j, t_1) = Subst(op_i, j, t_2)), where

$S_1, \ldots, S_k$ is the domain of op_i, and

Subst(op, j, t) is $op(x_1, \ldots, x_k)$ with t substituted for x_j.

3. Consequences and Exemptions

Exempts and *consequences* affect only the checking (see section 11.5) and do not affect the theory. We add to the grammar the productions:

trait	::= *traitId* : **trait** *traitBody* {*consequences*} {*exempts*}
consequences	::= **implies** *conseqProps* {*converts*}
conseqProps	::= *props*
converts	::= **converts** *conversion**,
conversion	::= **[** *sortedOp**, **]**
exempts	::= **exempts** *exemptTerms**
exemptTerms	::= **{ for all [** *varDcl**, **] }** *term**,

3.1. Context sensitive checking

conseqProps:

If the *props* of the *conseqProps* is appended to the *propPart* of the containing *trait*, the resulting *trait* must satisfy the checks of section 2.

exempts:

Each *term* must satisfy the checks of section 2.1.

4. Constrains Clauses

Constrains clauses affect only the checking (see section 11.4), not the theory. We add to the grammar the productions:

propPart	::= (**asserts** | *constrains*) *props*
constrains	::= **constrains** (*sortId* | *sortedOp**,) **so that**

4.1. Translation

constrains:

Replace the *constrains* by **asserts**.

5. Implicit Signatures and Partial OpForms

In the kernel language each *sortedOp* is an *opDcl*. Here we relax this restriction to allow omitted and partial signatures and omitted #'s. We add to the grammar the production:

sortedOp ::= *opId* { → *range* }

5.1. Context sensitive checking

There must be a unique mapping from occurrences of *sortedOp*'s to *opDcl*'s of the *traitBody* such that the translation described in section 5.2. produces a legal *traitBody* and for each *sortedOp*, *opDcl* pair:

The *opId*'s match, i.e.,

They are the same, or

They are both *opForms* and the one in the *sortedOp* is the same as the one in the *opDcl* with all #'s removed.

If the *sortedOp* includes → *range*, it is the same as the *range* of the *opDcl*.

5.2. Translation

The checking ensures that each occurrence of a *sortedOp* corresponds to a unique *opDcl*. The translation is simply to replace it by that *opDcl*.

6. Mixfix Operators

In the language presented thus far, all operators are treated as either nullary or prefix. Here we relax that restriction. We replace the grammar for *term* by:

term ::= *secondary* | **if** *secondary* **then** *secondary* **else** *term*

secondary ::= { *opSym* } *primary* (*opSym primary*)* { *opSym* }

primary ::= *sortedOp* { '(*term**, ') } | *varId* | '(*term* ')

6.1. Translation

equation:

It is necessary to resolve the grammatical ambiguity between the = connective in *equations* and the = *opSym*. In any *equation* the first occurrence of = that is not bracketed by parentheses or within an **if then else** is the *equation* connective, the remainder are *opSyms*. Parentheses can be used to enforce any desired parsing.

term:

Translate each term of the form **if** b **then** t_1 **else** t_2 into a term of the form **ifThenElse**(b, t_1, t_2).

secondary:

Translate each *secondary* containing *opSym*'s into a *primary* of the form *opId* '(*term**, '), where

opId is derived by replacing each *primary* in the *secondary* by #.

*term**, is the sequence of *primary*'s.

primary:

After the previous translations have been performed, remove the outer parentheses from *primary*'s of the form '(*term* ').

7. Boolean Terms as Equations

It is convenient to use terms of sort Bool as axioms. We add to the grammar the production:

equation ::= *term*

7.1. Context sensitive checking

The *term* must be of sort Bool.

7.2. Translation

Replace the *term* by the *equation*

term = true

8. External References

We add to the kernel grammar the productions:

traitBody	::= *externals simpleTrait*
externals	::= {*assumes*} {*imports*} {*includes*}
assumes	::= **assumes** *traitRef**,
imports	::= **imports** *traitRef**,
includes	::= **includes** *traitRef**,
traitRef	::= *traitId*
conseqProps	::= *traitRef**, *props*

8.1. Context sensitive checking

externals:

Recursive *externals* are not permitted; i.e., the *traitId* of the containing *trait* may not appear in an *externals*, nor in any partial translation of a *traitRef* in its *externals*.

8.2. Translation

The translation of a *trait* is derived bottom-up; i.e., before a trait with *traitRefs* is translated, each of its *traitRefs* is replaced by the translation of the *trait* labeled by that *traitRef*'s *traitId*. Let T be a *trait* whose *simpleTrait* is S and let E consist of the translations of the *traitRef*'s in T's *externals*. The translation of T consists of:

An *opPart* containing S's *opDcls* and E's *opDcls*,
A *propPart** containing S's *propPart*'s and E's *propPart*'s,
An *exempts* containing T's *exemptTerms* and E's *exemptTerms*, and
A *consequences* containing the *props* of
    T's *conseqProps*,
    the *propParts* of the translations of the *traitRef*'s in T's *conseqProps*, and
    E's *consequences*.

9. Modifications

We add to the grammar the productions:

traitRef ::= *traitId* {*exclusion*} {*renaming*}
exclusion ::= **without** [*oldOp**,]
renaming ::= **with** [(*sortRename* | *opRename*)*,]
sortRename ::= *sortId* **for** *oldSort*
oldSort ::= *sortId*
opRename ::= *opId* **for** *oldOp*
oldOp ::= *sortedOp*

9.1. Context sensitive checking

traitRef:

No *sortedOp* may occur more than once as an *oldOp*.

No *sortId* may occur more than once as an *oldSort*.

Each *oldSort* must appear in an *opDcl* in the translation of the *trait* labeled by the *traitId*.

There must be a unique mapping from *oldOp*'s to *opDcl*'s of the translation of the *trait* labeled by the *traitId*, such that for each *oldOp*, *opDcl* pair:

The *opId*'s match (see section 5.1),

If the *oldOp* includes *domain*, it is the same as the *domain* of the *opDcl*.

If the *oldOp* includes → *range*, it is the same as the *range* of the *opDcl*.

9.2. Translation

The translation of the *trait* labeled by the *traitId* of the *traitRef* is modified by applying first the *exclusion*, then the *opRename*'s, and finally the *sortRename*'s:

For each *oldOp* in the *exclusion*, delete each *bylist*, *equation*, and *term* containing the *opDcl* to which it maps and then delete all remaining occurrences of that *opDcl*.

Then, simultaneously, for each *opRename*, replace the *opId* part of each occurrence of the *opDcl* to which the *oldOp* maps by the *opId* of the *opRename*.

Finally, simultaneously, for each *sortRename*, replace each occurrence of its *oldSort* by its *sortId*.

10. Implicit Incorporation of Boolean, IfThenElse, and Equality

Three traits, Boolean, IfThenElse, and Equality, are implicitly incorporated into various other traits to assure uniform meanings for the operators they constrain.

10.1. Translation

Append the *traitRef* Boolean to the *imports* of each trait except Boolean.

Append the *traitRef* IfThenElse **with** [T1 **for** T] to the *imports* of each trait containing a term of the form **if** b **then** t_1 **else** t_2 in which t_1 and t_2 have the same sort, T1.

Append the *traitRef* Equality **with** [T1 **for** T] to the *traitRef** of the *conseqProps* of each trait (except Equality) containing a term of the form $t_1 = t_2$ in which t_1 and t_2 have the same sort, T1.

10.2. Built-in traits

```
Boolean: trait
    introduces
        true: → Bool
        false: → Bool
        ~#: Bool → Bool
        #&#: Bool, Bool → Bool
        #|#: Bool, Bool → Bool
        #⇒#: Bool, Bool → Bool
        #.equal#: Bool, Bool → Bool
    asserts Bool generated by [ true, false ]
        for all [ b: Bool ]
            ~true = false
            ~false = true
            (true & b) = b
            (false & b) = false
            (true | b) = true
            (false | b) = b
            (true ⇒ b) = b
            (false ⇒ b) = true
            (true .equal b) = b
            (false .equal b) = ~b
    implies converts [ ~, &, |, ⇒, .equal ]
IfThenElse: trait
    introduces ifThenElse: Bool, T, T → T
    asserts for all [ t1, t2: T ]
        ifThenElse(true, t1, t2) = t1
        ifThenElse(false, t1, t2) = t2
    implies converts [ ifThenElse ]
```

Equality: **trait**
introduces # = #: T, T → Bool
asserts T **partitioned by** [=]
for all [*x, y, z:* T]
$(x=x)$
$(x=y) = (y=x)$
$((x=y) \& (y=z)) \Rightarrow (x=z)$

11. Semantic Checking

In addition to the syntactic constraints specified above, we require that each *trait* be logically consistent, discharge the assumptions of the traits it is built from, be a conservative extension of its *imports*, be properly constraining, and imply its *consequences*.

11.1. Consistency

A *traitBody* is *consistent* if its associated theory does not contain the equation
true:→Bool = false:→Bool

11.2. Assumptions

Let A(T) be all of the *assumes* of the traits imported or included in T, and R(T) be the result of translating T after removing these *assumes*. A(T) is *discharged* by T if the theory associated with the translation of each *traitRef* of A(T) is a subset of the theory associated with R(T).

11.3. Imports

The theory associated with a *trait* must be a *conservative extension* of the theory associated with the translation of each *traitRef* in its *imports*; i.e., if *trait* T1 imports T2 and W is a *wff* of T2, W is in the theory associated with T1 if and only if it is in the theory associated with T2.

11.4. Constraints

A *propPart* is *properly-constraining* if it implies properties of only the operators in its *constrains*. The occurrence of a *sortId* in a *constrains* stands for the list of all *sortedOp*'s in the containing *trait*'s *opPart* whose *signatures* include that *sortId*.

Let T be a *trait* and P be the *propPart* **constrains** *sortedOp**, **so that** *props*. P is properly-constraining in the trait consisting of T plus P if and only if each *wff* in the theory associated with T plus P is also in the theory associated with T or else contains ops in *sortedOp**.

Note that, since the translation of a *traitRef* converts **constrains** to **asserts**, this check is performed only on *traits* in which **constrains** appears explicitly.

11.5. Consequences

A *trait* ***implies*** its ***consequences*** if the theory associated with its ***conseqProps*** is a subset of the theory associated with the *trait* and the [*sortedOp**,] in each ***converts*** is convertible. Convertibility is defined using the theory and ***exempts*** of a *trait*.

conseqProps:

The theory associated with ***conseqProps*** must be a subset of the theory of the *trait* in which the ***consequences*** appears. The theory associated with a ***conseqProps*** is the theory associated with the *traitbody:*

includes *traitRef**, *opPart* **asserts** *props*

where *traitRef**, and *props* form the ***conseqProps***, and *opPart* is the *opPart* of the *trait* in which the ***consequences*** appears.

Note that an ***exclusion***, but not a ***renaming***, can invalidate a consequence that has been locally checked.

conversion:

Let C be a ***conversion***. For each term, t, that contains no variables of any sort appearing in a ***generators*** in the containing trait, the theory of the containing trait must either

contain an equation t = u,

where u contains no *sortedOp* appearing in C's *sortedOp**, or

contain an equation t' = u,

where t' is a subterm of t, and u is an instantiation of a ***term*** appearing in an ***exempts*** of the containing trait.

12. Reference Grammar for The Larch Shared Language

trait ::= *traitId* : **trait** *traitBody* {*consequences*} {*exempts*}
traitBody ::= *externals simpleTrait*
externals ::= {*assumes*} {*imports*} {*includes*}
assumes ::= **assumes** *traitRef**,
imports ::= **imports** *traitRef**,
includes ::= **includes** *traitRef**,
traitRef ::= *traitId* {*exclusion*} {*renaming*}
exclusion ::= **without** [*oldOp**,]
renaming ::= **with** [(*sortRename* | *opRename*)*,]
sortRename ::= *sortId* **for** *oldSort*
oldSort ::= *sortId*
opRename ::= *opId* **for** *oldOp*
oldOp ::= *sortedOp*
sortedOp ::= *opDcl* | *opId* { → *range* }
simpleTrait ::= {*opPart*} *propPart**
opPart ::= **introduces** *opDcl**
opDcl ::= *opId* : *signature*
signature ::= *domain* → *range*
domain ::= *sortId**,
range ::= *sortId*
propPart ::= (**asserts** | *constrains*) *props*
constrains ::= **constrains** (*sortId* | *sortedOp**,) **so that**
props ::= *generators* partitions* axioms**
generators ::= *sortId* **generated** *bylist**,
partitions ::= *sortId* **partitioned** *bylist**,
bylist ::= **by** [*sortedOp**,]
axioms ::= **for all** [*varDcl**,] *equation**
varDcl ::= *varId**, : *sortId*
equation ::= *term* { = *term* }
term ::= *secondary* | **if** *secondary* **then** *secondary* **else** *term*
secondary ::= { *opSym* } *primary* (*opSym primary*)* { *opSym* }
primary ::= *sortedOp* { '(*term**, ') } | *varId* | '(*term* ')
opId ::= *alphaNumeric* + | *opForm*
opForm ::= { # } *opSym* (# *opSym*)* { # }
opSym ::= *specialChar* + | . *alphaNumeric* +
traitId ::= *alphaNumeric* +
sortId ::= *alphaNumeric* +
varId ::= *alphaNumeric* +
consequences ::= **implies** *conseqProps* {*converts*}
conseqProps ::= *traitRef**, *props*
converts ::= **converts** *conversion**,
conversion ::= [*sortedOp**,]
exempts ::= **exempts** *exemptTerms**
exemptTerms ::= { **for all** [*varDcl**,] } *term**,

Towards A Larch Shared Language Handbook

Contents

Basic properties of single operators, including binary relations

Associative, Commutative, Idempotent, Relation, TotalRelation, Reflexive, Irreflexive, Transitive, ReflexiveTransitive, Symmetric, Antisymmetric, Equivalence

Ordering relations

PartialOrder, TotalOrder, OrderEquivalence, OrderEquality, PartialOrderWithEquality, TotalOrderWithEquality, DerivedOrders, PartiallyOrdered, Ordered

Group theory

LeftIdentity, RightIdentity, Identity, LeftInverse, RightInverse, Inverse, Abelian, Semigroup, Monoid, Group, AbelianSemigroup, AbelianMonoid, AbelianGroup, Distributive

Simple numeric types

Ordinal, Cardinal, Cardinal2

Simple data structures

Pair, Triple, FiniteMapping

Container properties

Container, Singleton, IsEmpty, Size, AdditiveSize, Join, ElementEquality, Member, ElemCount, Delete, Containment, Next, Rest, Remainder, Index

Container classes

SetBasics, BagBasics, CollectionExtensions, SetIntersection, Set, Bag, Enumerable, InsertionOrdered, Stack, Queue, Dequeue, Sequence, SubSequence, String, PriorityQueue

Generic operators on containers

CoerceContainer, Reduce, SomePass, AllPass, Sift, PairwiseExtension, PointwiseImage

Nonlinear structures

BinaryTree, BasicGraph, Connectivity, Graph

Rings, fields, and numbers

Ring, RingWithUnit, InfixInverse, Integer, Field, Rational

Lattices

ExtremalBound, Semilattice, Lattice

Enumerated data types

Enumerated, Rainbow, Character

Display traits

Coordinate, Illumination, Boundary, Transform, Displayable, Picture, Contents, Component, ComponentCoercion, View, Display

Preface

This collection of traits is a companion to the Larch Shared Language Reference Manual. We hope that it will serve three distinct purposes:

Provide a set of components that can be directly incorporated into other specifications,

Provide a set of models upon which other specifications can be based, and

Help people to better understand the Larch Shared Language by providing a set of illustrative examples.

In line with our first goal, we have tried to isolate the "smallest useful increments" of specification that it might be reasonable to use in other specifications. In particular, we have tried to provide traits that will make it convenient to specify the weak assumptions that characterize many of the more widely applicable specifications. This is particularly evident in the sections titled "Container properties" and Container classes." The traits in these sections are smaller and more numerous than is typical in "from scratch" specifications. This sometimes leads to a somewhat overstructured appearance.

In line with our second goal, in addition to traits that we expect to be directly incorporated in specifications, we have included a number of traits intended primarily as patterns. The section titled "Generic operators on containers" contains several such traits. Because of the arity of the operators, it will frequently be awkward to incorporate these traits.

In line with our third goal we have stressed familiar examples. Since they describe well-understood mathematical entities, many of the traits, e.g., Integer, are atypically complete. In general, we expect most specifications to supply constraints, rather than complete definitions. The section on Display traits is more typical in this respect.

The support tools envisioned for Larch are not yet available. Transcriptions of traits in this chapter have been mechanically checked for some properties; some errors may not have been detected and some transcription errors may have crept in. They should be given the same sort of credence as carefully written programs that have not been checked by a compiler.

Comments on the clarity of these specifications and on their "correctness" (relative to generally accepted definitions of the names used) are welcome. We also solicit contributions of further widely useful traits—either accompanied by specifications, or as challenges to specifiers.

Conventions

If a generic trait constrains only one interesting sort, the identifier T is used to denote it.

If a trait constrains a "containing" sort and an "element" sort, the identifiers C and E are used.

If a trait constrains a single binary operation, the infix symbol #○# is used.

If a trait constrains a single binary relation, the infix identifier #⊛# is used.

If there would be no information in a **constrains** (e.g., because there is only one operator), **asserts** is used.

Basic Properties of Single Operators, Including Binary Relations

Associative: **trait**
introduces #○#: T, T → T
asserts for all [*x*, *y*, *z*: T] $(x \circ y) \circ z = x \circ (y \circ z)$

Commutative: **trait**
introduces #○#: T, T → Range
asserts for all [*x*, *y*: T] $x \circ y = y \circ x$

Idempotent: **trait**
introduces op: T → T
asserts for all [*x*: T] $op(op(x)) = op(x)$

Relation: **trait**
introduces #Ⓡ#: T, T → Bool

TotalRelation: **trait**
includes Relation
asserts for all [*x*, *y*: T] $(x \,Ⓡ\, y) \mid (y \,Ⓡ\, x)$

Reflexive: **trait**
includes Relation
asserts for all [*x*: T] $x \,Ⓡ\, x$

Irreflexive: **trait**
includes Relation
asserts for all [*x*: T] $\sim(x \,Ⓡ\, x)$

Transitive: **trait**
includes Relation
asserts for all [*x*, *y*, *z*: T] $((x \,Ⓡ\, y) \,\&\, (y \,Ⓡ\, z)) \Rightarrow (x \,Ⓡ\, z)$

ReflexiveTransitive: **trait**
includes Reflexive, Transitive

Symmetric: **trait**
includes Relation
asserts for all [*x*, *y*: T] $(x \,Ⓡ\, y) = (y \,Ⓡ\, x)$
implies Commutative **with** [Ⓡ for ○, Bool for Range]

Antisymmetric: **trait**
includes Relation
asserts for all [*x*, *y*: T] $\sim((x \,Ⓡ\, y) \,\&\, (y \,Ⓡ\, x))$
implies Irreflexive

Equivalence: **trait**
includes ReflexiveTransitive **with** [.eq for Ⓡ],
Symmetric **with** [.eq for Ⓡ]

Ordering Relations

PartialOrder: **trait**
imports ReflexiveTransitive **with** [$\leq$ **for** ®]

TotalOrder: **trait**
includes PartialOrder, TotalRelation **with** [$\leq$ **for** ®]

OrderEquivalence: **trait**
assumes PartialOrder
introduces #.eq#: T, T → Bool
constrains .eq **so that for all** [*x*, *y*: T] $(x \text{ .eq } y) = (x \leq y) \,\&\, (y \leq x)$
implies Equivalence
converts [.eq]

OrderEquality: **trait**
assumes PartialOrder
includes OrderEquivalence **with** [= **for** .eq], Equality

PartialOrderWithEquality: **trait**
includes PartialOrder, OrderEquality

TotalOrderWithEquality: **trait**
includes TotalOrder, OrderEquality

DerivedOrders: **trait**
assumes PartialOrder
introduces
#<#: T, T → Bool
#≥#: T, T → Bool
#>#: T, T → Bool
constrains < **so that for all** [*x*, *y*: T] $(x < y) = ((x \leq y) \,\&\, (\sim(y \leq x)))$
constrains ≥ **so that for all** [*x*, *y*: T] $(x \geq y) = (y \leq x)$
constrains > **so that for all** [*x*, *y*: T] $(x > y) = (y < x)$
implies Transitive **with** [< **for** ®],
Transitive **with** [> **for** ®],
Antisymmetric **with** [< **for** ®],
Antisymmetric **with** [> **for** ®],
PartialOrder **with** [≥ **for** ≤]
converts [<, ≥, >]

PartiallyOrdered: **trait**
imports PartialOrderWithEquality
includes DerivedOrders
implies PartialOrderWithEquality **with** [≥ **for** ≤]

Ordered: **trait**
imports TotalOrderWithEquality
includes DerivedOrders
implies PartiallyOrdered, TotalOrderWithEquality **with** [≥ **for** ≤]

Group Theory

LeftIdentity: **trait**
  introduces
    #○#: T, T → T
    unit: → T
  asserts for all [*x*: T] unit ○ *x* = *x*

RightIdentity: **trait**
  introduces
    #○#: T, T → T
    unit: → T
  asserts for all [*x*: T] *x* ○ unit = *x*

Identity: **trait includes** LeftIdentity, RightIdentity

LeftInverse: **trait**
  assumes LeftIdentity
  introduces inv: T → T
  asserts for all [*x*: T] inv(*x*) ○ *x* = unit

RightInverse: **trait**
  assumes RightIdentity
  introduces inv: T → T
  asserts for all [*x*: T] *x* ○ inv(*x*) = unit

Inverse: **trait**
  assumes Identity
  includes LeftInverse, RightInverse

Abelian: **trait imports** Commutative **with** [T **for** Range]

Semigroup: **trait includes** Associative, Equality

Monoid: **trait includes** Semigroup, LeftIdentity

Group: **trait**
  includes Monoid, LeftInverse
  implies RightIdentity, RightInverse

AbelianSemigroup: **trait includes** Abelian, Semigroup

AbelianMonoid: **trait**
  includes Abelian, Monoid
  implies RightIdentity

AbelianGroup: **trait includes** Abelian, Group

Distributive: **trait**
  introduces
    #+#: T, T → T
    #*#: T, T → T
  asserts for all [*x*, *y*, *z*: T]
    $x*(y + z) = (x*y) + (x*z)$
    $(y + z)*x = (y*x) + (z*x)$

Simple Numeric Types

Ordinal: **trait**
includes PartialOrder **with** [= **for** .eq, Ord **for** T],
OrderEquivalence **with** [= **for** .eq, Ord **for** T]
introduces
first: → Ord
succ: Ord → Ord
asserts Ord **generated by** [first, succ]
Ord **partitioned by** [$\leq$]
for all [*x*, *y*: Ord]
first $\leq x$
~(succ(x) $\leq$ first)
succ(x) $\leq$ succ(y) = $x \leq y$
implies TotalOrderWithEquality **with** [Ord **for** T]
converts [$\leq$, =]

Cardinal: **trait**
imports Ordinal **with** [0 **for** first, Card **for** Ord]
includes DerivedOrders **with** [Card **for** T]
introduces
1: → Card
#+#: Card, Card → Card
#*#: Card, Card → Card
#$\ominus$#: Card, Card → Card
constrains 1 **so that** 1 = succ(0)
constrains +, * **so that for all** [*x*, *y*: Card]
$x + 0 = x$
x + succ(y) = succ($x + y$)
x*0 = 0
x*succ(y) = $x + (x*y)$
constrains $\ominus$ **so that for all** [*x*, *y*: Card]
$0 \ominus x = 0$
$x \ominus 0 = x$
succ(x) $\ominus$ succ(y) = $x \ominus y$
implies Cardinal2
Card **generated by** [1, +, $\ominus$]
Card **partitioned by** [$\geq$], **by** [=], **by** [<], **by** [>]
for all [*x*, *y*: Card] $x \leq y = ((x \ominus y) = 0)$
converts [1, $\ominus$, +, *, =, $\leq$, $\geq$, <, >]

```
Cardinal2: trait                    % Alternate definition for comparison
    includes AbelianMonoid with [ + for O, 0 for unit, Card for T ],
        AbelianMonoid with [ * for O, 1 for unit, Card for T ],
        Distributive with [ Card for T ],
        Ordered with [ Card for T ]
    introduces
        #⊖#: Card, Card → Card
        succ: Card → Card
    asserts Card generated by [ 0, 1, + ]
        for all [ x, y: Card ]
            x < (x + 1)
            (x + y) ⊖ y = x
            0 ⊖ x = 0
            succ(x) = x + 1
    implies Cardinal
```

Simple Data Structures

```
Pair: trait
    introduces
        ⟨#, #⟩: T1, T2 → C
        #.first: C → T1
        #.second: C → T2
    asserts C generated by [ ⟨#, #⟩ ]
        C partitioned by [ .first, .second ]
        for all [ f: T1, s: T2 ]
            ⟨f, s⟩.first = f
            ⟨f, s⟩.second = s
    implies converts [ .first, .second ]
Triple: trait
    introduces
        ⟨#, #, #⟩: T1, T2, T3 → C
        #.first: C → T1
        #.second: C → T2
        #.third: C → T3
    asserts C generated by [ ⟨#, #, #⟩ ]
        C partitioned by [ .first, .second, .third ]
        for all [ f: T1, s: T2, t: T3 ]
            ⟨f, s, t⟩.first = f
            ⟨f, s, t⟩.second = s
            ⟨f, s, t⟩.third = t
    implies converts [ .first, .second, .third ]
FiniteMapping: trait
    assumes Equality with [ Index for T ]
    introduces
        new: → C
        bind: C, Index, E → C
        #[#]: C, Index → E
        defined: C, Index → Bool
    asserts C generated by [ new, bind ]
        C partitioned by [ #[#], defined ]
    constrains C so that
        for all [ c: C, i, il: Index, e: E ]
            bind(c, il, e)[i] = if i = il then e else c[i]
            ~defined(new, i)
            defined(bind(c, il, e), i) = (i = il) | defined(c, i)
    implies converts [ #[#], defined ]
    exempts for all [ i: Index ] new[i]
```

Container Properties

Container: **trait**

introduces
new: → C
insert: C, E → C
asserts C **generated by** [new, insert]

Singleton: **trait**

assumes Container
introduces singleton: E → C
constrains singleton **so that for all** [*e:* E]
singleton(*e*) = insert(new, *e*)
implies converts [singleton]

IsEmpty: **trait**

assumes Container
introduces isEmpty: C → Bool
asserts for all [*c:* C, *e:* E]
isEmpty(new)
~isEmpty(insert(*c*, *e*))
implies converts [isEmpty]

Size: **trait**

assumes Container
imports Cardinal
introduces size: C → Card
constrains size **so that**
size(new) = 0

AdditiveSize: **trait**

assumes Container
includes Size
constrains size, insert **so that for all** [*c:* C, *e:* E]
size(insert(*c*, *e*)) = size(*c*) + 1
implies converts [size]

Join: **trait**

assumes Container
introduces #.join#: C, C → C
constrains .join **so that for all** [*c*, *c1:* C, *e:* E]
c .join new = *c*
c .join insert(*c1*, *e*) = insert(*c* .join *c1*, *e*)
implies converts [.join]

ElementEquality: **trait imports** Equality **with** [E **for** T]

Member: **trait**

assumes Container, ElementEquality
introduces #∈#: E, C → Bool
constrains ∈, insert **so that for all** [*c:* C, *e*, *e1:* E]
~(*e* ∈ new)
e ∈ insert(*c*, *e1*) = (*e* = *e1*) | (*e* ∈ *c*)
implies converts [∈]

ElemCount: **trait**

assumes Container, ElementEquality
imports Cardinal
introduces count: C, E → Card
constrains count, insert **so that for all** [*e*, *e1:* E, *c:* C]
count(new, *e*) = 0
count(insert(*c*, *e*), *e1*) = count(*c*, *e*) + (**if** *e* = *e1* **then** 1 **else** 0)
implies converts [count]

Delete: **trait**

assumes Container
introduces delete: C, E → C
constrains delete **so that for all** [*e:* E] delete(new, *e*) = new

Containment: **trait**

assumes Container
includes PartiallyOrdered **with** [⊂ **for** <, ⊃ **for** >, ⊆ **for** ≤, ⊇ **for** ≥, C **for** T]
constrains C **so that for all** [*e:* E, *c:* C] *c* ⊆ insert(*c*, *e*)
implies for all [*c:* C] new ⊆ *c*

Next: **trait**

assumes Container
introduces next: C → E
constrains next, insert **so that for all** [*e:* E] next(insert(new, *e*)) = *e*
exempts next(new)

Rest: **trait**

assumes Container
introduces rest: C → C
constrains rest, insert **so that for all** [*e:* E] rest(insert(new, *e*)) = new
exempts rest(new)

Remainder: **trait**

assumes Container, Rest
imports Cardinal
introduces remainder: C, Card → C
constrains remainder **so that for all** [*c:* C, *i:* Card]
remainder(*c*, 0) = *c*
remainder(*c*, *i* + 1) = remainder(rest(*c*), *i*)
implies converts [remainder]

Index: **trait**

assumes Container, Next, Rest
imports Cardinal
introduces #[#]: C, Card → E
constrains #[#] **so that for all** [*c:* C, *i:* Card]
c[1] = next(*c*)
c[(*i* + 1)] = rest(*c*)[*i*]
implies converts [#[#]]
exempts for all [*c:* C] *c*[0]

Container Classes

SetBasics: **trait**

assumes ElementEquality, Container **with** [{} **for new**]
includes Size **with** [{} **for new**],
Member **with** [{} **for new**]
introduces delete: C, E → C
constrains C **so that**
C **partitioned by** [∈]
for all [*s:* C, *e, el:* E]
size(insert(*s, e*)) = size(*s*) + (**if** *e* ∈ *s* **then** 0 **else** 1)
el ∈ delete(*s, e*) = (*el* ∈ *s*) & (~(*e* = *el*))
implies Delete **with** [{} **for new**]
converts [size, delete, ∈]

BagBasics: **trait**

assumes ElementEquality, Container **with** [{} **for new**]
imports AdditiveSize **with** [{} **for new**],
ElemCount **with** [{} **for new**]
includes Member **with** [{} **for new**]
introduces delete: C, E → C
constrains C **so that**
C **partitioned by** [count]
for all [*b:* C, *e, el:* E]
count(delete(*b, e*), *el*) = count(*b, el*) − (**if** *e* = *el* **then** 1 **else** 0)
implies Delete **with** [{} **for new**]
converts [size, delete, count, ∈]

CollectionExtensions: **trait**

assumes ElementEquality, Container **with** [{} **for new**]
imports IsEmpty **with** [{} **for new**],
Singleton **with** [{} **for new**, {#} **for** singleton],
Containment **with** [{} **for new**],
Join **with** [{} **for new**, ∪ **for** .join]
includes Equality **with** [C **for** T]
implies converts [{#}, isEmpty, ∪]

SetIntersection: **trait**

assumes SetBasics
introduces ∩: C, C → C
constrains C **so that for all** [*s, s1:* C, *e, el:* E]
e ∈ (*s* ∩ *s1*) = (*e* ∈ *s*) & (*e* ∈ *s1*)
converts [∩]

Set: **trait**

assumes ElementEquality
imports SetBasics, SetIntersection
includes CollectionExtensions
implies Abelian **with** [∪ **for** ○, C **for** T],
Abelian **with** [∩ **for** ○, C **for** T]
converts [size, delete, ∈, ∩, ∪, {#}, isEmpty, =, ⊂, ⊃, ⊆, ⊇]

Bag: **trait**

assumes ElementEquality
imports BagBasics
includes CollectionExtensions
implies Abelian **with** [∪ **for** ○, C **for** T]
converts [size, delete, count, ∈, ∪, {#}, isEmpty, =, ⊂, ⊃, ⊆, ⊇]

Enumerable: **trait**

imports IsEmpty, Next, Rest
includes Container
constrains C **so that** C **partitioned by** [next, rest, isEmpty]

InsertionOrdered: **trait** % For assuming "Stack or Queue"

includes Enumerable
introduces isFIFO: → Bool
constrains next, rest, insert **so that for all** [*c:* C, *e:* E]
next(insert(*c*, *e*)) = **if** isEmpty(*c*) | isFIFO **then** *e* **else** next(*c*)
rest(insert(*c*, *e*)) = **if** isEmpty(*c*) | isFIFO **then** *c* **else** insert(rest(*c*), *e*)
implies converts [next, rest]

Stack: **trait**

includes InsertionOrdered **with** [push **for** insert, top **for** next, pop **for** rest,
true **for** isFIFO]
implies for all [*stk:* C, *e:* E]
top(push(*stk*, *e*)) = *e*
pop(push(*stk*, *e*)) = *stk*

Queue: **trait**

includes InsertionOrdered **with** [first **for** next, false **for** isFIFO]
implies for all [*q:* C, *e:* E]
first(insert(*q*, *e*)) = **if** isEmpty(*q*) **then** *e* **else** first(*q*)
rest(insert(*q*, *e*)) = **if** isEmpty(*q*) **then** new **else** insert(rest(*q*), *e*)

Dequeue: **trait**

includes Stack **with** [insert **for** push, first **for** top, rest **for** pop],
Stack **with** [enter **for** push, last **for** top, prefix **for** pop]
constrains C **so that for all** [*c:* C, *e*, *e1:* E]
insert(new, *e*) = enter(new, *e*)
insert(enter(*c*, *e*), *e1*) = enter(insert(*c*, *e1*), *e*)
implies Queue, Queue **with** [enter **for** insert, last **for** first, prefix **for** rest]
converts [insert, first, last, rest, prefix], [enter, first, last, rest, prefix]

Sequence: **trait**

imports Dequeue, AdditiveSize
includes Index **with** [first **for** next],
Join **with** [|| **for** join]
implies C **partitioned by** [size, #[#]]

SubSequence: **trait**

imports Sequence
includes Remainder **with** [#[#...] **for** remainder],
Remainder **with** [#[...#] **for** remainder, prefix **for** rest]

String: **trait**

imports Character
includes Sequence **with** [length **for** size, Char **for** E]

PriorityQueue: **trait**

assumes TotalOrder **with** [E **for** T]
includes Enumerable
constrains next, rest, insert **so that for all** [*q:* C, *e:* E]
next(insert(*q*, *e*)) = **if** isEmpty(*q*) **then** *e*
else if next(*q*) ≤ *e* **then** next(*q*) **else** *e*
rest(insert(*q*, *e*)) = **if** isEmpty(*q*) **then** new
else if next(*q*) ≤ *e* **then** insert(rest(*q*), *e*) **else** *q*
implies converts [next, rest, isEmpty]

Generic Operators on Containers

CoerceContainer: **trait**

assumes Container **with** [DC **for** C],
Container **with** [RC **for** C]
introduces coerce: DC → RC
constrains coerce **so that for all** [*dc:* DC, *e:* E]
coerce(new) = new
coerce(insert(*dc*, *e*)) = insert(coerce(*dc*), *e*)
implies converts [coerce]

Reduce: **trait**

assumes Enumerable,
RightIdentity **with** [E **for** T],
Associative **with** [E **for** T]
introduces reduce: C → E
constrains reduce **so that for all** [*c:* C]
reduce(*c*) = **if** isEmpty(*c*) **then** unit **else** next(*c*) ○ reduce(rest(*c*))
implies converts [reduce]

SomePass: **trait**

assumes Container
introduces
test: E, T → Bool
somePass: C, T → Bool
constrains somePass **so that for all** [*c:* C, *e:* E, *t:* T]
~somePass(new, *t*)
somePass(insert(*c*, *e*), *t*) = test(*e*, *t*) | somePass(*c*, *t*)
implies converts [somePass]

```
AllPass: trait
    assumes Container
    introduces
        test: E, T → Bool
        allPass: C, T → Bool
    constrains allPass so that for all [ c: C, e: E, t: T ]
        allPass(new, t)
        allPass(insert(c, e), t) = test(e, t) & allPass(c, t)
    implies converts [ allPass ]
Sift: trait
    assumes Container
    introduces
        test: E, T → Bool
        sift: C, T → C
    constrains sift so that for all [ c: C, e: E, t: T ]
        sift(new, t) = new
        sift(insert(c, e), t) = if test(e, t) then insert(sift(c, t), e) else sift(c, t)
    implies converts [ sift ]
PairwiseExtension: trait
    assumes InsertionOrdered
    introduces
        extOp: C, C → C
        elemOp: E, E → E
    constrains extOp so that for all [ c1, c2: C, e1, e2: E ]
        extOp(new, new) = new
        extOp(insert(c1, e1), insert(c2, e2)) = insert(extOp(c1, c2), elemOp(e1, e2))
    implies converts [ extOp ]
    exempts for all [ c: C, e: E ]
        extOp(new, insert(c, e)),
        extOp(insert(c, e), new)
PointwiseImage: trait
    assumes Container with [ DC for C, DE for E ],
        Container with [ RC for C, RE for E ]
    introduces
        extOp: DC → RC
        pointOp: DE → RE
    constrains extOp so that for all [ dc: DC, de: DE ]
        extOp(new) = new
        extOp(insert(dc, de)) = insert(extOp(dc), pointOp(de))
    implies converts [ extOp ]
```

Nonlinear Structures

BinaryTree: trait

imports Cardinal
introduces
⟨#⟩: E → C
⟨#, #⟩: C, C → C
#.left: C → C
#.right: C → C
size: C → Card
isLeaf: C→ Bool
content: C → E
constrains C **so that**
C **generated by** [⟨#⟩, ⟨#, #⟩]
C **partitioned by** [.left, .right, content, isLeaf]
for all [*tl, tr:* C, *e:* E]
(⟨*tl, tr*⟩).left = *tl*
(⟨*tl, tr*⟩).right = *tr*
size(⟨*e*⟩) = 1
size(⟨*tl, tr*⟩) = size(*tl*) + size(*tr*)
isLeaf(⟨*e*⟩)
~isLeaf(⟨*tl, tr*⟩)
content(⟨*e*⟩) = *e*
implies for all [*t:* C] isLeaf(*t*) = (size(*t*) = 1)
converts [.left, .right, size, isLeaf, content]
exempts for all [*tl, tr:* C, *e:* E] (⟨*e*⟩).left, (⟨*e*⟩).right, content(⟨*tl, tr*⟩)

BasicGraph: trait

assumes Equality **with** [Node **for** T]
imports Set **with** [NodeSet **for** C, Node **for** E],
Pair **with** [Edge **for** C, Node **for** T1, Node **for** T2]
introduces
empty: → Graph
addNode: Graph, Node → Graph
addEdge: Graph, Edge → Graph
nodes: Graph → NodeSet
adj: Node, Graph → NodeSet
constrains Graph **so that**
Graph **generated by** [empty, addNode, addEdge]
Graph **partitioned by** [nodes, adj]
for all [*g:* Graph, *e:* Edge, *n, n1:* Node]
nodes(empty) = {}
nodes(addNode(*g, n*)) = insert(nodes(*g*), *n*)
nodes(addEdge(*g, e*)) = insert(insert(nodes(*g*), *e*.first), *e*.second)
adj(*n*, empty) = {}
adj(*n*, addNode(*g, n1*)) = adj(*n, g*)
adj(*n*, addEdge(*g, e*)) =
if *n* = (*e*.first) **then** insert(adj(*n, g*), *e*.second) **else** adj(*n, g*)
implies converts [nodes, adj]

```
Connectivity: trait
    assumes Equality with [ Node for T ], BasicGraph
    introduces
        reach: NodeSet, Graph → NodeSet
        allReach: NodeSet, NodeSet, Graph → Bool
        connected: Graph → Bool
    constrains reach, allReach, connected so that
        for all [ g: Graph, e: Edge, ns, ns1: NodeSet, n: Node ]
            reach(ns, empty) = {}
            reach(ns, addNode(g, n)) = reach(ns, g)
            allReach({}, ns, g)
            allReach(insert(ns, n), ns1, g) =
            allReach(ns, ns1, g) & (ns1 ⊆ reach({n}, g))
            connected(g) = allReach(nodes(g), nodes(g), g)
    implies converts [ allReach, connected ]
Graph: trait
    assumes Equality with [ Node for T ]
    imports BasicGraph
    includes Connectivity,
        Connectivity with [ stronglyConnected for connected, pathReach for reach,
            allPathReach for allReach ]
    constrains reach, allReach, connected so that
        for all [ g: Graph, e: Edge, ns: NodeSet ]
            reach(ns, addEdge(g, e)) = reach(ns, g) ∪
                (if (e.first) ∈ ns then insert(reach({(e.second)}, g), (e.second))
                else if (e.second) ∈ ns then insert(reach({(e.first)}, g), (e.first))
                else {})
    constrains pathReach, allPathReach, stronglyConnected so that
        for all [ g: Graph, e: Edge, ns: NodeSet ]
            pathReach(ns, addEdge(g, e)) = pathReach(ns, g) ∪
                (if (e.first) ∈ ns
                    then insert(pathReach({(e.second)}, g), (e.second))
                    else {})
    implies converts [ reach, allReach, connected, pathReach, allPathReach,
        stronglyConnected ]
```

Rings, Fields, and Numbers

Ring: **trait**
includes AbelianGroup **with** [+ **for** ○, 0 **for** unit, −# **for** inv],
Semigroup **with** [* **for** ○],
Distributive

RingWithUnit: **trait**
includes Ring, Identity **with** [* **for** ○, 1 **for** unit]

InfixInverse: **trait**
assumes Inverse
introduces #⊘#: T, T → T
constrains #⊘# **so that for all** [*x, y:* T]
$x \oslash y = x \bigcirc \text{inv}(y)$
implies converts [#⊘#]

Integer: **trait**
includes RingWithUnit **with** [Int **for** T],
Ordered **with** [Int **for** T],
InfixInverse **with** [+ **for** ○, −# **for** inv, − **for** ⊘, Int **for** T]
asserts Int **generated by** [1, +, −#]
for all [*x:* Int]
$x < (x + 1)$
implies Rational **without** [$^{-1}$, /] **with** [Int **for** R]
converts [0, *, #−#, =, ≤, ≥, <, >]

Field: **trait**
includes RingWithUnit
introduces $\#^{-1}$: T → T
constrains *, $^{-1}$ **so that for all** [*x:* T]
$(x = 0) \mid ((x*(x^{-1})) = 1)$
exempts 0^{-1}

Rational: **trait**
includes Field **with** [R **for** T],
Ordered **with** [R **for** T],
InfixInverse **with** [+ **for** ○, −# **for** inv, − **for** ⊘, R **for** T],
InfixInverse **with** [* **for** ○, $\#^{-1}$ **for** inv, / **for** ⊘, R **for** T]
asserts
R **generated by** [1, +, −#, $^{-1}$]
for all [*x, y, z:* R]
$0 < 1$
$((x + z) < (y + z)) = (x < y)$
$(x = 0) \mid ((0 < (x^{-1})) = (0 < x))$
implies converts [0, *, #−#, /, =, ≤, ≥, <, >]

Lattices

ExtremalBound: **trait**

assumes PartialOrder
includes AbelianSemigroup **with** [.glb **for** O]
constrains .glb **so that for all** [*x*, *y*, *z*: T]
$(x \text{ .glb } y) \leq x$
$((z \leq x) \;\&\; (z \leq y)) \Rightarrow (z \leq (x \text{ .glb } y))$

Semilattice: **trait**

includes PartiallyOrdered,
ExtremalBound,
ExtremalBound **with** [$\geq$ **for** $\leq$, .lub **for** .glb]
introduces $\bot$: $\rightarrow$ T
constrains $\bot$ **so that for all** [*x*: T]
$x \geq \bot$
implies AbelianMonoid **with** [$\bot$ **for** unit, .lub **for** O]

Lattice: **trait**

includes Semilattice
introduces T: $\rightarrow$ T
constrains T **so that for all** [*x*: T]
$x \leq$ T
implies Lattice **with** [T **for** $\bot$, $\bot$ **for** T, .glb **for** .lub, .lub **for** .glb,
$\geq$ **for** $\leq$, $\leq$ **for** $\geq$, $>$ **for** $<$, $<$ **for** $>$]

Enumerated Data Types

```
Enumerated: trait
    imports Ordinal
    includes Ordered
    introduces
        first: → T
        last: → T
        succ: T → T
        pred: T → T
        ord: T → Ord
    asserts T generated by [ first, succ ]
        T partitioned by [ ord ]
        for all [ x, y: T ]
            ord(first) = first
            ord(succ(x)) = if x = last then ord(last) else succ(ord(x))
            pred(succ(x)) = if x = last then pred(last) else x
            x ≤ y = ord(x) ≤ ord(y)
    implies T generated by [ last, pred ]
        for all [ x: T ]
            succ(pred(x)) = if x = first then succ(first) else x
            first ≤ x
            x ≤ last
    converts [ =, ≤, ≥, <, > ]
Rainbow: trait
    includes Enumerated with [ Color for T ]
    introduces
        red: → Color
        orange: → Color
        yellow: → Color
        green: → Color
        blue: → Color
        violet: → Color
    asserts
        Color generated by [ red, orange, yellow, green, blue, violet ]
        first = red
        last = violet
        succ(red) = orange
        succ(orange) = yellow
        succ(yellow) = green
        succ(green) = blue
        succ(blue) = violet
    implies converts [ pred, last, ord, =, ≤, ≥, <, >, red, orange, yellow, green, blue,
        violet ],
        [ succ, first, ord, =, ≤, ≥, <, >, red, orange, yellow, green, blue, violet ]
Character: trait includes Enumerated with [ Char for T ]
% For each programming language there will be mappings from character and string constants to
% terms in the shared language. Because of the variety of character orderings and notations for
% constants, these definitions are not likely to be portable across programming languages.
```

Display Traits

```
% The following traits represent a fairly straightforward translation of the specifications in
% "Formal Specification as a Design Tool" (CSL-80-1). We have not attempted to improve the
% design presented there, merely to translate it into Larch.

Coordinate: trait introduces minus: Coordinate, Coordinate → Coordinate

Illumination: trait introduces combine: Illumination, Illumination → Illumination

Boundary: trait introduces apply: Boundary, Coordinate → Bool

Transform: trait introduces apply: Transformation, Coordinate → Coordinate

Displayable: trait
    introduces
        appearance: T, Coordinate → Illumination
        in: T, Coordinate → Bool

Picture: trait
    assumes Boundary, Transform, Illumination,
        Displayable with [ Contents for T ]
    includes Displayable with [ Picture for T ]
    introduces makePicture: Contents, Boundary, Transformation → Picture
    constrains Picture so that
        Picture generated by [ makePicture ]
        for all [ cn: Contents, b: Boundary, t: Transformation, cd: Coordinate ]
            appearance(makePicture(cn, b, t), cd) =
                appearance(cn, apply(t, cd))
            in(makePicture(cn, b, t), cd) = apply(b, cd)
    implies converts [ appearance: Picture, Coordinate → Illumination,
        in: Picture, Coordinate → Bool ]

Contents: trait
    assumes Coordinate, Illumination, Displayable with [ Component for T ]
    includes Displayable with [ Contents for T ]
    introduces
        empty: → Contents
        addComponent: Contents, Component, Coordinate → Contents
    constrains Contents so that
        Contents generated by [ empty, addComponent ]
        for all [ cn: Contents, cm: Component, cd, cd1: Coordinate ]
            appearance(addComponent(cn, cm, cd1), cd) =
                if in(cm, minus(cd, cd1))
                then (if in(cn, cd)
                        then combine(appearance(cm, minus(cd, cd1)),
                        appearance(cn, cd))
                        else appearance(cm, minus(cd, cd1)))
                else appearance(cn, cd)
            ~in(empty, cd)
            in(addComponent(cn, cm, cd1), cd) =
                in(cm, minus(cd, cd1)) | in(cn, cd)
    implies converts [ appearance: Contents, Coordinate → Illumination,
        in: Contents, Coordinate → Bool ]
    exempts for all [ cd: Coordinate ] appearance(empty, cd)
```

Component: **trait**

assumes Displayable **with** [View **for** T],
Displayable **with** [Text **for** T],
Displayable **with** [Figure **for** T]
includes ComponentCoercion **with** [View **for** T, coerceView **for** coerce],
ComponentCoercion **with** [Text **for** T, coerceText **for** coerce],
ComponentCoercion **with** [Figure **for** T, coerceFigure **for** coerce]

ComponentCoercion: **trait**

assumes Displayable
includes Displayable **with** [Component **for** T]
introduces coerce: T → Component
constrains Component **so that for all** [*t:* T, *cd:* Coordinate]
appearance(coerce(*t*), *cd*) = appearance(*t*, *cd*)
in(coerce(*t*), *cd*) = in(*t*, *cd*)

View: trait

assumes Displayable **with** [Picture **for** T],
Equality **with** [PictureId **for** T],
Container **with** [IdList **for** C, PictureId **for** E],
Coordinate
includes Displayable **with** [View **for** T]
introduces
empty: → View
addPicture: View, Coordinate, PictureId, Picture → View
findPictures: View, Coordinate → IdList
deletePicture: View, PictureId → View
constrains View **so that**
View **generated by** [empty, addPicture]
for all [*v:* View, *cd*, *cd1:* Coordinate, *id*, *id1:* PictureId, *p:* Picture]
appearance(addPicture(*v*, *cd1*, *id*, *p*), *cd*) =
if in(*p*, minus(*cd*, *cd1*)) **then** appearance(*p*, minus(*cd*, *cd1*))
else appearance(*v*, *cd*)
~in(empty, *cd*)
in(addPicture(*v*, *cd1*, *id*, *p*), *cd*) = (in(*p*, minus(*cd*, *cd1*)) | in(*v*, *cd*))
findPictures(empty, *cd*) = new
findPictures(addPicture(*v*, *cd1*, *id*, *p*), *cd*) =
if in(*p*, minus(*cd*, *cd1*)) **then** insert(*id*, findPictures(*v*, *cd*))
else findPictures(*v*, *cd*)
deletePicture(empty, *id*) = empty
deletePicture(addPicture(*v*, *cd1*, *id1*, *p*), *id*) =
if *id* .eq *id1* **then** *v* **else** addPicture(deletePicture(*v*, *id*), *cd*, *id1*, *p*)
implies converts [findPictures, deletePicture,
appearance: View, Coordinate → Illumination,
in: View, Coordinate → Bool]
exempts for all [*cd:* Coordinate] appearance(empty, *cd*)

Display: **trait**

assumes Boundary, Transform, Illumination, Coordinate,
Equality **with** [PictureId **for** T],
Container **with** [IdList **for** C, PictureId **for** E]
includes Picture, Contents, Component, View

References

[ADJ 78]
J.A. Goguen, J.W. Thatcher, and E.G. Wagner, "Initial Algebra Approach to the Specification, Correctness, and Implementation of Abstract Data Types," in R.T. Yeh (ed.), *Current Trends in Programming Methodology, Vol. IV, Data Structuring*, Prentice-Hall, Englewood Cliffs, 1978.

[Burstall and Goguen 77]
R.M. Burstall and J.A. Goguen, "Putting Theories Together to Make Specifications," *Proc. 5th International Joint Conference on Artificial Intelligence*, Cambridge, MA, 1977, 1045-1058.

[Burstall and Goguen 81]
R.M. Burstall and J.A. Goguen, "An Informal Introduction to Specifications Using CLEAR," in R. Boyer and J. Moore (eds.), *The Correctness Problem in Computer Science*, Academic Press, New York, 1981, 185-213.

[Forgaard 83]
R. Forgaard, "A Program for Generating and Analyzing Term Rewriting Systems," S.M. Thesis, Laboratory for Computer Science, Massachusetts Institute of Technology, to appear, 1983.

[Guttag 75]
J.V. Guttag, "The Specification and Application to Programming of Abstract Data Types," Ph.D. Thesis, Computer Science Department, University of Toronto, 1975, 1-149.

[Guttag and Horning 80]
J.V. Guttag and J.J. Horning, "Formal Specification as a Design Tool," *Proc. ACM Symposium on Principles of Programming Languages*, Las Vegas, Jan. 1980, 251-261.

[Guttag and Horning 83]
J.V. Guttag and J.J. Horning, "An Introduction to the Larch Shared Language," *Proc. IFIP Congress '83*, Paris, 1983.

[Guttag, Horning, and Wing 82]
J.V. Guttag, J.J. Horning, and J.M. Wing, "Some Notes on Putting Formal Specifications to Productive Use," *Science of Computer Programming*, vol. 2, Dec. 1982, 53-68.

[Kownacki 83]
R. Kownacki, "A User's Guide to the Larch Shared Language Specification Checker," Laboratory for Computer Science, Massachusetts Institute of Technology, to appear, 1983.

[Lescanne 83]
P. Lescanne, "Computer Experiments with the REVE Term Rewriting System Generator," *Proc. ACM Symposium on Principles of Programming Languages*, Austin, Jan. 1983, 99-108.

[Musser 80]
D.R. Musser, "Abstract Data Type Specification in the Affirm System,"
IEEE Transactions on Software Engineering vol. 1, 1980, 24-32.

[Wand 79]
M. Wand, "Final Algebra Semantics and Data Type Extensions,"
Journal of Computer and System Sciences, vol. 19, 1979, 27-44.

[Wing 83]
J.M. Wing, "A Two-Tiered Approach to Specifying Programs,"
Ph.D. Thesis, Laboratory for Computer Science, Massachusetts Institute of Technology,
May 1983.

[Zachary 83]
J.L. Zachary, "A Syntax-Directed Specification Editor,"
S.M. Thesis, Laboratory for Computer Science, Massachusetts Institute of Technology,
Mar. 1983.

This blank page was inserted to preserve pagination.

CS-TR Scanning Project
Document Control Form

Date : 4/4/96

Report # LCS-TR-307

Each of the following should be identified by a checkmark:
Originating Department:

☐ Artificial Intellegence Laboratory (AI)
☒ Laboratory for Computer Science (LCS)

Document Type:

☒ Technical Report (TR) ☐ Technical Memo (TM)
☐ Other:_____

Document Information

Number of pages: 55 (62-IMAGES)
Not to include DOD forms, printer instructions, etc... original pages only.

Originals are:
☒ Single-sided or
☐ Double-sided

Intended to be printed as :
☐ Single-sided or
☒ Double-sided

Print type:
☐ Typewriter ☐ Offset Press ☐ Laser Print
☐ InkJet Printer ☒ Unknown ☐ Other:_____

Check each if included with document:
☒ DOD Form (2) ☐ Funding Agent Form ☒ Cover Page
☒ Spine ☐ Printers Notes ☐ Photo negatives
☐ Other: _____

Page Data:

Blank Pages (by page number): _____

Photographs/Tonal Material (by page number): _____

Other (note description/page number):

Description : Page Number:

(A) IMAGE MAP! (1-55) UNITED TITLE PAGE, 2-55 (56-62) [redacted] SCANCONTROL COVERS&SPINE (1 PAGE), DOD (2), TRGT'S (3)

(B) NOTE! SOME PAGES HAVE MARKS FROM WHITEOUT USE.

Scanning Agent Signoff:
Date Received: 4/4/96 Date Scanned: 4/5/96 Date Returned: 4/11/96

Scanning Agent Signature: Michael W. Cook

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER: MIT/LCS/TR-307

2. GOVT ACCESSION NO.:

3. RECIPIENT'S CATALOG NUMBER:

4. TITLE (and Subtitle): Preliminary Report on The Larch Shared Language

5. TYPE OF REPORT & PERIOD COVERED: Interim Research

6. PERFORMING ORG. REPORT NUMBER: MIT/LCS

7. AUTHOR(s): John V. Guttag and J. J. Horning

8. CONTRACT OR GRANT NUMBER(s): DARPA/DOD N00014-75-C-0661; NSF MCS-811984 6

9. PERFORMING ORGANIZATION NAME AND ADDRESS:
MIT Laboratory for Computer Science
545 Technology Square
Cambridge, MA 02139

10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS:

11. CONTROLLING OFFICE NAME AND ADDRESS:
DARPA/DOD/IPTO
1400 Wilson Boulevard
Arlington, VA 22209

12. REPORT DATE: October 1983

13. NUMBER OF PAGES: 55

14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office):
Office of Naval Research/Dept of Navy
Information Systems Program
Arlington, VA 22217

15. SECURITY CLASS. (of this report): Unclassified

15a. DECLASSIFICATION/DOWNGRADING SCHEDULE:

16. DISTRIBUTION STATEMENT (of this Report):

Approved for Public Release; distribution is unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report):

Unlimited

18. SUPPLEMENTARY NOTES:

19. KEY WORDS (Continue on reverse side if necessary and identify by block number):

Algebraic specification, specification language

20. ABSTRACT (Continue on reverse side if necessary and identify by block number):

Each member of the Larch family of formal specification languages has a component derived from a programming language and another component common to all programming languages. We call the former interface languages, and the latter the Larch Shared Language.

This report presents version 1.0 of the Larch Shared Language. It begins with

...continued

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER: MIT/LCS/TR-307	2. GOVT ACCESSION NO.
4. TITLE (and Subtitle): Preliminary Report on the Larch Shared Language	5. TYPE OF REPORT & PERIOD COVERED: Interim Research
7. AUTHOR(s): John V. Guttag, James J. Horning, Jeannette M. Wing	8. CONTRACT OR GRANT NUMBER(s): N00014-75-C-0661 & MCS76-22004
9. PERFORMING ORGANIZATION NAME AND ADDRESS: MIT Laboratory for Computer Science, 545 Technology Square, Cambridge, MA 02139	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS: DARPA/DOD/IPTO, 1400 Wilson Boulevard, Arlington, VA 22209	12. REPORT DATE: October 19, 1982
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office): Office of Naval Research/Dept of Navy, Information Systems Program, Arlington, VA 22217	13. NUMBER OF PAGES: 66
	15. SECURITY CLASS. (of this report): Unclassified
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for Public Release; distribution is unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

Unlimited

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Algebraic specification, specification language

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

Each member of the Larch family of formal specification languages has a component derived from a programming language and another component common to all programming languages. We call the former interface languages, and the latter the Larch Shared Language.

This report presents version 1.0 of the Larch Shared Language. It begins with ...continued

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Classified

Scanning Agent Identification Target

Scanning of this document was supported in part by the **Corporation for National Research Initiatives,** using funds from the **Advanced Research Projects Agency** of the **United states Government** under Grant: **MDA972-92-J1029.**

The scanning agent for this project was the **Document Services** department of the **M.I.T Libraries.** Technical support for this project was also provided by the **M.I.T. Laboratory for Computer Sciences.**

Scanned

Date: 04/08/1996

M.I.T. Libraries
Document Services